

		M2		
INPUTS	CHANNELS		2 (BUILT IN XY MIC)	
	MIC INPUT	MIC TYPE	Unidirectional	
		SENSITIVITY	-42 dB, 1 kHz at 1 Pa	
		INPUT GAIN	Adjustment unnecessary (dual AD converter circuits used)	
		MAX SOUND PRESSURE INPUT	135 dB SPL	
OUTPUTS	HEADPHONE	CONNECTOR	1/8" stereo mini jack	
		MAXIMUM OUTPUT LEVEL	20 mW +20 mW (32 Ω load)	
	BUILT-IN SPEAKER		500mW/8Ω mono speaker	
RECORDING	RECORDING MEDIA		4GB–32GB microSDHC cards 64GB–1TB microSDXC cards	
	WAV	SUPPORTED FORMATS	44.1/48/96kHz 32-bit float mono/stereo BWF and iXML	
		MAXIMUM SIMULTANEOUS RECORDING TRACKS	2 (BUILT IN XY MIC)	
POWER SUPPLIES	BATTERIES		2 AA	
	AC ADAPTER		ZOOM AD-17 (DC 5 V/1 A) • USB bus power is supported.	
DISPLAY	LCD		LCD with backlight (96×64)	
USB	CONNECTOR		USB Type-C	
	MASS STORAGE	CLASS	USB 2.0 High Speed	
	AUDIO INTERFACE WITH REC	CLASS		USB 2.0 High Speed
		SAMPLING RATE		48kHz
		BIT RATE		24-bit/32-bit float
		CHANNELS		2 in/2 out
ESTIMATED CONTINUOUS OPERATION TIME USING BATTERIES	48 kHz/32-bit float, 2ch recording to microSDHC card		Alkaline batteries: about 11 hours	
INCLUDED ITEMS			QUICK GUIDE WINDSCREEN MIC CLIP	